



**Einstelltabelle**

**Tableaux d'ajustement**

**Adjusting table**

Zw.-sohle Semelle Ext.-slide	Bereich D Gamme D Diameter D	WP-Halter Porte plaq. Ins. holder	Pos. Pos. Pos.	Ausgl.-gew. Contrepoid Counterw.	Korrektur $\alpha$ Correction $\alpha$ Correction $\alpha$
317.221 Ø150-200	Ø 150-180 Ø 175-200	626.161 626.162	Pos. 1 Pos. 1	317.104	150
317.222 Ø200-270	Ø 198-228 Ø 224-254 Ø 233-263 Ø 259-289	626.161 626.162 626.161 626.162	Pos. 1 Pos. 1 Pos. 2 Pos. 2	317.105	200
317.223 Ø270-340	Ø 268-298 Ø 294-324 Ø 303-333 Ø 329-359	626.161 626.162 626.161 626.162	Pos. 1 Pos. 1 Pos. 2 Pos. 2	317.105	270
317.224 Ø340-410	Ø 338-368 Ø 364-394 Ø 373-403 Ø 399-429	626.161 626.162 626.161 626.162	Pos. 1 Pos. 1 Pos. 2 Pos. 2	317.105	340
317.225 Ø410-480	Ø 408-438 Ø 434-464 Ø 443-473 Ø 469-499	626.161 626.162 626.161 626.162	Pos. 1 Pos. 1 Pos. 2 Pos. 2	317.105	410
317.226 Ø480-550	Ø 478-508 Ø 504-534 Ø 513-543 Ø 539-569	626.161 626.162 626.161 626.162	Pos. 1 Pos. 1 Pos. 2 Pos. 2	317.105	480
317.227 Ø550-620	Ø 548-578 Ø 574-604 Ø 583-613 Ø 609-639	626.161 626.162 626.161 626.162	Pos. 1 Pos. 1 Pos. 2 Pos. 2	317.105	550

Zw.-sohle Semelle Ext.-slide	Bereich D Gamme D Diameter D	WP-Halter Porte plaq. Ins. holder	Pos. Pos. Pos.	Ausgl.-gew. Contrepoid Counterw.	Korrektur $\alpha$ Correction $\alpha$ Correction $\alpha$
317.231 Ø620-690	Ø 618-648 Ø 644-674 Ø 653-683 Ø 679-709	626.161 626.162 626.161 626.162	Pos. 1 Pos. 1 Pos. 2 Pos. 2	317.105	620
317.232 Ø690-760	Ø 688-718 Ø 714-744 Ø 723-753 Ø 749-779	626.161 626.162 626.161 626.162	Pos. 1 Pos. 1 Pos. 2 Pos. 2	317.105	690
317.233 Ø760-830	Ø 758-788 Ø 784-814 Ø 793-823 Ø 819-849	626.161 626.162 626.161 626.162	Pos. 1 Pos. 1 Pos. 2 Pos. 2	317.105	760
317.234 Ø830-900	Ø 828-858 Ø 854-884 Ø 863-893 Ø 889-919	626.161 626.162 626.161 626.162	Pos. 1 Pos. 1 Pos. 2 Pos. 2	317.105	830
317.235 Ø900-970	Ø 898-928 Ø 924-954 Ø 933-963 Ø 959-989	626.161 626.162 626.161 626.162	Pos. 1 Pos. 1 Pos. 2 Pos. 2	317.105	900
317.236 Ø970-1'040	Ø 968-998 Ø 994-1024 Ø 1003-1033 Ø 1029-1059	626.161 626.162 626.161 626.162	Pos. 1 Pos. 1 Pos. 2 Pos. 2	317.105	970
317.237 Ø1'040-1'110	Ø 1038-1068 Ø 1064-1094 Ø 1073-1103 Ø 1099-1129	626.161 626.162 626.161 626.162	Pos. 1 Pos. 1 Pos. 2 Pos. 2	317.105	1'040
317.238 Ø1'110-1'180	Ø 1108-1138 Ø 1134-1164 Ø 1143-1173 Ø 1169-1199	626.161 626.162 626.161 626.162	Pos. 1 Pos. 1 Pos. 2 Pos. 2	317.105	1'110

**Beispiel:**

Bearbeitungs-Ø = 335 H7  
Zw.-Sohle = 317.223  
WP-Halter = 626.162  
Position = 2  
Skala =  $D - \alpha = 335 - 270 = \underline{65}$

**Example:**

$D = \text{Ø } 335$   
Semelle = 317.223  
Porte plaq. = 626.162  
Position = 2  
Echelle =  $D - \alpha = 335 - 270 = \underline{65}$

**Example:**

Bore Dia. = Ø 335  
Ext. slide = 317.223  
Ins. holder = 626.162  
Position = 2  
Scale =  $D - \alpha = 335 - 270 = \underline{65}$